

JT – Series Wall Mount Reverse Osmosis Systems

FLEXEON JT – Series Wall Mount Reverse Osmosis Systems offer high production capacities and are fully equipped with a computer controller, TDS monitor, multi-stage booster pump, low energy membranes and a sediment filter mounted on a corrosion-resistant, powder-coated aluminum frame.

FLEXEON JT – Series Wall Mount Reverse Osmosis Systems models are available in capacities of 2,000 and 4,000 gallons per day and feature the EZMount™ two-piece wall mounting system for easy installation. An optional mobile stand is also available to convert any of the models into floor standing units.

Features

- Minitrol Computer Controller
 - Multi Color LED Indicator Status Light
 - Pre-Treatment Lockout
 - Tank Level Input
 - Low Pressure Monitoring and Alarm
 - AXEON HF1 – Series Low Energy Membranes
 - AXEON PVC – Series Membrane Housings
 - AXEON 5 – Micron Sediment Pre-Filter
 - AXEON by Pentek® Big Grey Cartridge Housing
 - AXEON Permeate and Concentrate Flow Meters
 - AXEON 0 – 100 psi Pre-Filter Pressure Gauge
 - AXEON 0 – 100 psi Post-Filter Pressure Gauge
- AXEON 0 – 300 psi Pump Pressure Gauge
 - AXEON 0 – 300 psi Concentrate Pressure Gauge
 - Feed Low Pressure Switch
 - AXEON by GC Feed Solenoid Valve
 - AXEON 316L Stainless Steel Concentrate Valve
 - Goulds® Multi-Stage Booster Pump
 - John Guest® Push/Pull Fittings with Locking Safety Clips
 - White Powder Coated Aluminum Frame



FLEXEON JT – Series Wall Mount Reverse Osmosis System
Shown with Concentrate Recycle Option

Product Specifications		
Models	JT – 2000	JT – 4000
Design		
Standard Recovery Rate %	31	47
Rejection and Flow Rates		
Nominal Salt Rejection %	99	99
Membranes		
Membrane Quantity	1	2
Membrane Size	4040	4040
Systems Dimensions		
Approximate Dimensions* L x W x H (in / cm)	12 X 48 X 49 / 30.5 X 122.0 X 124.5	12 X 48 X 49 / 30.5 X 122.0 X 124.5
Approximate Weight (lbs / kg)	150 / 68.0	175 / 79.4

* Does not include operating space requirements.

Know Higher Standards™

