

GC – Series Solenoid Valve Kits

GC – Series Solenoid Valves are debris tolerant valves that are manufactured from high strength, corrosion free, UV resistant nylon reinforced plastic. They feature a high flow design, bypass handle for valve actuation in the case of power failure and are a cost effective solution to regulate flow control.



Features

- Water Tight Sealed Molded Coil
- 3 – Meter (118 in) Length Cord
- PVC Jacketed Extension Cable
- Normally Closed Operation
- 18/3 Wire Size
- Class H (6.5 VA draw)
- UL Recognized, CE
- Manual Bypass Valve

Part Number	End Connections (in)	Flow Range (gpm / lpm)	Voltage (volts)	Minimum Operating Pressure (psi)	Maximum Operating Pressure (psi)
209420	1/2 FNPT	5 – 100 / 18.90 – 378.00	24	5	100
208920	1/2 FNPT	5 – 100 / 18.90 – 378.00	110	5	100
209419	1/2 FNPT	5 – 100 / 18.90 – 378.00	220	5	100
210193	3/4 FNPT	5 – 20 / 18.90 – 75.60	24	10	125
208786	3/4 FNPT	5 – 20 / 18.90 – 75.60	110	10	125
208787	3/4 FNPT	5 – 20 / 18.90 – 75.60	220	10	125
210194	1 FNPT	5 – 100 / 18.90 – 378.00	24	5	100
208788	1 FNPT	5 – 35 / 18.90 – 132.30	110	10	125
208789	1 FNPT	5 – 35 / 18.90 – 132.30	220	10	125

Know Higher Standards™

