

# S-200C MEMBRANE ANTISCALANT

**AXEON® S-200C Membrane Antiscalant** is a highly effective antiscalant, specially formulated for feedwater with the highest levels of metal oxides, silica and scale-forming minerals. It is effective over a wide range of concentrations, and does not flocculate dissolved polymers such as residual coagulants or iron or aluminum-rich silica. Use of this product is recommended for reducing the operating and capital costs of reverse osmosis (RO), nanofiltration (NF) and ultrafiltration (UF) systems. It inhibits polymerization of reactive silica, and disperses colloidal (non-reactive) silica.



## BENEFITS

- Highly effective in retarding polymerization and precipitation of silica.
- Effectively controls inorganic scales over a large concentration range.
- Certified under ANSI/NSF Standard 60 for drinking water production.
- Compatible with major manufacturer's RO, NF, and UF membranes.
- Does not flocculate dissolved iron/aluminum oxide/silicate complexes.
- May be used diluted or undiluted.
- Effective in feedwaters with a pH range of 5.0-10.0.
- Particularly effective for controlling coagulation of colloidal silica by aluminum, iron and heavy metal salts.



Tested and Certified by NSF International against ANSI/NSF Standard 60 for material requirements only.

COMPONENT

## PACKAGING

- Liquid: 5 gallons (27 kg), 55 gallons (295 kg)

## DOSING RECOMMENDATIONS

In the useful dosage range of 1-10 mg/q, control of a wide range of inorganic scales along with reactive and non-reactive silica at high levels. By monitoring the concentrate stream and trend charts, optimal dosage can be achieved for the control of silica gels and scales which form chemically linked foulants prone to flocculation with organic materials.

Part Numbers	Description
208950	Chemical, antiscalant, concentrate silica, 5 gal, S-200C, AXEON
210192	Chemical, antiscalant, concentrate silica, 55 gal, S-200C, AXEON

## SPECIFICATIONS

Qualities	Liquid <sup>A</sup>
Appearance	Clear, colorless liquid
pH	≤ 2.0
Specific Gravity	1.45 ± 0.10

A. For further details on proper dosage, please refer back to the product label. SDS available upon request.